

# Understanding the composition dependent charge qubit operations in a dual-gate Al<sub>x</sub>Ga<sub>1-x</sub>As nanowire FET using NEGF approach



Nilayan Paul<sup>1</sup>, Basudev Nag Chowdhury<sup>1</sup> and Sanatan Chattopadhyay<sup>1,2</sup>

<sup>1</sup>Department of Electronic Science, University of Calcutta, India


<sup>2</sup>Centre for Research in Nanoscience and Nanotechnology (CRNN), University of Calcutta

Paper ID: 013

## INTRODUCTION


- □ Double quantum dot (DQD) devices for scalable quantum computers: control over quantum state manipulation; compatibility with already existing state-of-the-art fabrication processes.
- □ Challenges: very short dephasing time (~1-10 ns) and operational at ultra-low temperature operation (~mK-µK) [3-5].
- ☐ Voltage-tunable quantum dots (VTQDs) potentially free from the above limitations.
- Present work: Al composition dependent charge qubit operation and performance of a dual-gate Al<sub>x</sub>Ga<sub>1-x</sub>As nanowire FET with voltage-tunable DQDs.

# SCHEME OF THE CHARGE QUBIT DEVICE



- Nanowire diameter: 5 nm; Gate length: 3 nm (each); Gate separation: 3 nm; Channel length (source to drain): 20 nm.
- □ Single electron occupancy of VTQDs ⇒ reduced charge noise.
- □ Energy gap between VTQD states >> phonon energy @ RT ⇒ negligible phonon scattering.

# SCHEME OF THE CHARGE QUBIT OPERATION



Non-adiabatic voltage pulses eliminate the need for microwave driven state manipulation!

## MATHEMATICAL MODELING

 $\square$  Retarded Green's function, G(E), to model the charge qubit operation [1] is:

$$G(E) = [E - H_{ISO} - \Sigma_S - \Sigma_D]^{-1}$$

 $H_{ISO}$ : Isolated nanowire Hamiltonian with two gates;  $\Sigma_{S/D}$ : source/drain self-energies which incorporate non-unitary evolutions of the quantum state [2].

- $\square \Sigma_{S} \rightarrow$  'Initialization';  $\Sigma_{D} \rightarrow$  'Measurement'.
- $\Box$  Gate voltages  $V_{G1(2)}$  are non-decohering!
- $\square$   $G(E) \rightarrow LDOS: D(E) \rightarrow n(z) = \int D(E) dE$
- ☐ 'Measurement' → Pulse current at drain; to obtain employ Landauer formula:

$$I_0 = \frac{2e}{h} \int dE T(E) (f_S(E) - f_D(E - V_D))$$

□ Dephasing time  $\rightarrow$  decay of pulse current in time domain for continuous  $\Delta V_{G2}$  pulses at gate-2.

$$I(t) = I_0 F.T._{E \to t} [G_{ISO}(E)\Sigma_D(E)G(E)]$$

- $\Box$   $F.T._{E \to t}$   $\Rightarrow$  Fourier transform from energy to time domain.
- □ Positional basis:  $|L>/|R> \rightarrow \underline{logical\ qubit}$  states where superposed state expressed as.


$$|\psi\rangle = \cos\left(\frac{\theta}{2}\right)|L\rangle + e^{i\phi}\sin\left(\frac{\theta}{2}\right)|R\rangle$$

- $\square$   $n(z) \rightarrow \theta$ ; manipulated by non-adiabatic  $\Delta V_{G2}$  pulses at gate-2.
- $\square$  Local phase of  $G(E) \rightarrow \phi$ ; manipulated by varying  $V_{G1}$  keeping  $V_{G2}$  fixed.


# RESULTS AND DISCUSSIONS

- ☐ High AI composition leads to high effective mass (m\*); high bandgap; low permittivity.
- $\Box$  High m\*  $\rightarrow$  reduced tunneling probability.
- ☐ High bandgap/low permittivity observed to enhance tunnel barriers.

#### 1. Bloch sphere coverage




□ High m\* → reduced tunneling probability and degraded inter-dot coupling ⇒ reduced Bloch sphere coverage, <u>less</u> information can be encoded!



- □ High Al composition → weak inter-dot coupling (high m\*, high tunnel barriers) ⇒ reduced anti-crossing energy.
- ☐ Qubit current also <u>significantly reduced!</u>

#### 3. Dephasing time

Al composition (x)	Dephasing Time $(T_2)$ (ns)
x = 0: GaAs	82.4
$x = 0.2$ : $Al_{0.2}Ga_{0.8}As$	97.5
$x = 0.4$ : $AI_{0.4}Ga_{0.6}As$	141.0
$x = 0.6$ : $AI_{0.6}Ga_{0.4}As$	175.3
$x = 0.8$ : $AI_{0.8}Ga_{0.2}As$	201.3
x = 1: AlAs	272.1



### CONCLUSION

- ☐ Higher Al content ⇒reduced Bloch sphere coverage.
- □ Lower Al content ⇒ improved inter-dot tunneling, enhanced anti-crossing energy.
- □ Al composition dependent dephasing time: ~10x 20x higher than previously reported values (~10 ns) for GaAs based DQDs at 100 mK [3-5].
- ☐ High dephasing times at the cost of reduced anti-crossing, qubit current and degraded Bloch sphere coverage.
- ☐ Dimension dependent strong quantization reduces the <u>charge noise</u> and <u>phonon scattering</u> phenomena.

#### REFERENCES

- 1. B. Nag Chowdhury et. al., Adv. Quantum Technol., 6(4), 2200072 (2023).
- 2. N. Paul et. al., arXiv (2023), DOI: <a href="https://doi.org/10.48550/arXiv.2304.10554">https://doi.org/10.48550/arXiv.2304.10554</a> (Communicated to J. Comp. Electronics)
- 3. Petersson et. al., Phys. Rev. Lett. 105(24), 246804 (2010).
- 4. Hayashi et. al., Phys. Rev. Lett. 91(22), 226804 (2003).
- 5. Van der Wiel et. al., Rev. Mod. Phys., 75(1), 1 (2002).